



**Galvanized Flexible Conduit - Super Flexible Type**

**Material:** Steel

**Application:** used primarily in dry areas where it would be impractical to install EMT or other non-flexible conduit



TOPELE#	Trade Size	Metric Designator	Inside Diameter		Outside Diameter		Min. Bend Radius(mm)	Meters / Coil
			Min(mm)	Max(mm)	Min(mm)	Max(mm)		
GFC01	3/8"	12	10.82	12.09	14.22	15.49	25	100
GFC02	1/2"	16	18.44	19.97	21.84	23.37	38	100
GFC03	3/4"	21	22.64	24.17	26.54	28.07	45	50
GFC04	1"	27	28.82	30.85	33.02	35.05	55	50
GFC05	1-1/4"	35	34.47	36.50	39.37	41.40	62	25
GFC06	1-1/2"	41	41.79	44.33	46.99	49.53	90	25
GFC07	2"	53	54.29	56.83	59.69	62.23	110	20
GFC08	2-1/2"	63	65.44	70.52	72.64	77.72	130	20
GFC09	3"	78	78.14	83.22	85.34	90.42	160	10
GFC10	4"	103	103.54	108.62	110.74	115.85	210	10

**Galvanized Flexible Conduit - Greenfield Type**

**Material:** Steel

**Application:** used primarily in dry areas where it would be impractical to install EMT or other non-flexible conduit



TOPELE#	Trade Size	Metric Designator	Inside Diameter		Outside Diameter		Min. Bend Radius(mm)	Meters / Coil
			Min(mm)	Max(mm)	Min(mm)	Max(mm)		
FMC01	3/8"	12	9.52	9.96	14.22	15.49	50	100
FMC02	1/2"	16	15.88	16.38	21.84	23.37	75	100
FMC03	3/4"	21	20.62	21.21	26.54	28.07	100	50
FMC04	1"	27	25.40	26.42	33.02	35.05	125	50
FMC05	1-1/4"	35	31.75	33.02	39.37	41.40	160	25
FMC06	1-1/2"	41	38.10	40.01	46.99	49.53	190	25
FMC07	2"	53	50.80	52.83	59.69	62.23	225	20
FMC08	2-1/2"	63	63.50	66.04	72.64	77.72	320	20
FMC09	3"	78	76.20	78.74	85.34	90.42	*	10
FMC10	4"	103	101.60	104.14	110.74	115.82	*	10

